

TR&A P-Metric Load & Inflation Table

* Never exceed the tire's maximum load as indicated on the sidewall.

Replacement tires must be of a size, load range, and load capacity (by inflation) that are capable of supporting the load of the vehicle's originally installed (O.E.) tires.

Single Load per tire in pounds
(LL) indicates Light Load Index

Tire Size	Standard Load Index	Extra Load Index	Tire Load Limits (lbs.) at Various Inflation Pressures (PSI)							
			26	29	32	35	36	38	41	42
P145/80R12	74		705	739	783	816				
P155/65R13	74	77	617	672	728	783	805	838	882	908
P155/70R13	75	77	728	772	805	853		882	908	
P155/80R13	79		838	882	926	959				
P165/70R13	78		816	860	904	937				
P165/80R13	83		926	981	1025	1069				
P175/50R13	72	74	672	705	739	783		805	827	
P175/70R13	82		893	948	992	1036				
P175/80R13	86		1025	1080	1135	1179				
P185/70R13	85		992	1036	1091	1135				
P185/80R13	90		1124	1190	1246	1301				
P195/70R13	88		1080	1135	1190	1246				
P205/60R13	86		1014	1069	1124	1179				
P205/70R13	91		1179	1235	1301	1356				
P215/50R13	84		948	992	1047	1091				
P165/70R14	81		783	849	915	981	1019			
P175/65R14	81	84	882	937	981	1019		1058	1102	
P175/70R14	84		948	1003	1047	1102				
P175/75R14	86		1014	1069	1124	1168				
P185/60R14	82		904	948	1003	1047				
P185/65R14	85		970	1025	1069	1124				
P185/70R14	87		1036	1091	1146	1201				
P185/75R14	89		1113	1168	1235	1290				
P195/60R14	85		981	1036	1091	1135				
P195/65R14	88	90	1058	1113	1168	1235		1279	1323	
P195/70R14	90		1135	1201	1257	1312				
P195/75R14	92	95	1213	1279	1345	1400		1466	1521	
P205/60R14	88		1069	1135	1190	1235				
P205/70R14	93		1235	1301	1367	1433				
P205/75R14	95	98	1323	1400	1466	1532		1587	1653	
P215/60R14	91		1168	1224	1290	1345				
P215/70R14	96		1345	1411	1488	1554				
P215/75R14	98		1433	1521	1587	1664				

Tire Size	Standard Load Index	Extra Load Index	Tire Load Limits (lbs.) at Various Inflation Pressures (PSI)							
			26	29	32	35	36	38	41	42
P225/45R14	86		970	1038	1104	1168				
P225/60R14	94		1257	1323	1389	1455				
P225/70R14	98		1455	1532	1609	1675				
P225/75R14	101		1554	1642	1720	1797				
P235/60R14	96		1356	1422	1499	1565				
P245/50R14	93		1246	1312	1378	1433				
P245/60R14	98		1455	1532	1609	1675				
P265/50R14	98		1422	1499	1565	1642				
P175/50R15	75		661	716	772	827	853			
P175/60R15	81		783	849	915	981	1019			
P175/65R15	84		849	926	992	1069	1102			
P185/55R15	82		805	871	948	1014	1047			
P185/60R15	84		948	1003	1047	1102				
P185/65R15	86		1014	1069	1124	1168				
P195/50R15	81		893	937	981	1019				
P195/55R15	84	87	959	1014	1058	1102		1157	1201	
P195/60R15	87		1036	1091	1146	1190				
P195/65R15	89		1113	1168	1235	1279				
P195/75R15	94		1279	1345	1411	1477				
P205/50R15	84		970	1014	1069	1113				
P205/55R15	87		1047	1102	1157	1201				
P205/60R15	90		1124	1190	1246	1301				
P205/65R15	92	95	1213	1279	1334	1400		1455	1521	
P205/70R15	95		1301	1367	1433	1499				
P205/75R15	97	99	1389	1466	1532	1598		1664	1709	
P215/50R15	87		1047	1102	1157	1201				
P215/60R15	93		1224	1290	1345	1411				
P215/65R15	95		1312	1378	1455	1510				
P215/70R15	97		1411	1488	1554	1620				
P215/75R15	100	102	1510	1587	1664	1742		1808	1874	
P225/45R15	81 (LL)		882	926	981	1019				
P225/50R15	90		1124	1190	1246	1301				
P225/55R15	92		1224	1290	1345	1389				
P225/60R15	95		1312	1389	1455	1521				
P225/70R15	100		1521	1598	1675	1753				
P225/75R15	102	105	1631	1720	1797	1874		1951	2028	
P235/60R15	98		1422	1499	1565	1642				
P235/65R15	100		1521	1609	1687	1764				
P235/70R15	102		1642	1731	1808	1896				
P235/75R15	105	108	1753	1852	1940	2028		2105	2183	

Application of Load Inflation Tables
Version 2020-7

Tire Size	Standard Load Index	Extra Load Index	Tire Load Limits (lbs.) at Various Inflation Pressures (PSI)							
			26	29	32	35	36	38	41	42
P245/50R15	95	97	1301	1367	1444	1499		1565	1609	
P245/60R15	100		1521	1609	1687	1753				
P245/70R15	105	108	1764	1852	1951	2028		2116	2194	
P255/55R15	100		1510	1587	1664	1742				
P255/60R15	102	105	1631	1720	1808	1885		1962	2039	
P255/65R15	105		1753	1852	1940	2028				
P255/70R15	108	110	1885	1984	2083	2183		2271	2337	
P265/50R15	99		1488	1565	1642	1720				
P265/70R15	110		2017	2127	2227	2337				
P265/75R15	112		2160	2282	2392	2469				
P275/35R15	91		1047	1135	1224	1312	1356			
P275/50R15	101		1587	1675	1753	1830				
P275/60R15	107		1863	1962	2050	2149				
P285/70R15	115		2293	2414	2535	2679				
P295/50R15	105	108	1786	1885	1973	2061		2149	2205	
P295/55R15	109		1830	1962	2094	2216	2271			
P295/60R15	111		2105	2216	2326	2403				
P295/65R15	114		2271	2392	2502	2601				
P305/50R15	108	110	1896	1995	2094	2194		2282	2337	
P305/70R15	116		2227	2381	2535	2679	2756			
P315/60R15	116		2359	2480	2601	2756				
P325/50R15	112		2116	2238	2337	2447				
P345/55R15	118		2557	2701	2833	2910				
P185/55R16	83		827	893	970	1036	1074			
P185/60R16	86		904	981	1058	1135	1168			
P185/65R16	88		948	1036	1113	1190	1235			
P195/50R16	83		937	981	1036	1074				
P195/55R16	86		1003	1058	1113	1168				
P195/60R16	89		981	1069	1157	1235	1279			
P195/65R16	92		1069	1157	1257	1345	1389			
P205/40R16	79	83	798	855	910	963	996	1023	1074	
P205/45R16	83		827	893	970	1036	1074			
P205/50R16	86	89	1014	1069	1124	1168		1213	1279	
P205/55R16	89		1091	1157	1213	1279				
P205/60R16	91	94	1179	1246	1301	1356		1422	1477	
P205/65R16	94		1268	1334	1400	1477				
P205/70R16	96		1356	1433	1499	1565				
P215/40R16	77 (LL)		739	783	838	882	908			
P215/45R16	80 (LL)		805	860	915	970	992			
P215/50R16	89		1091	1157	1213	1279				